

Care and use instructions for your Mr Jan Gear SUIT

Every Suit is made in Europe with care and to stringent quality standards. In order for you to enjoy your suit for years to come, please take note of the following care and use instructions.

Cleaning SUIT

Your SUIT, you need to rinse after every use with freshwater. Do not wash in the washing machine or use detergents, bleaching agents or conditioners. Dry the suit inside out first, then the outer shell.

Seals

All suit seals are made from natural rubber (Latex) of the highest quality or from Neoprene to ensure maximum mobility and comfort. Natural rubber is, however, a delicate material. Any type of solvent and oil (especially sun protection products) can damage the material and are therefore not to come into contact with any seals. Hot and cold temperatures as well as UV radiation can also cause damage. Furthermore, squeezing, folding or bending of the seals can lead to cracks in the material.

Important:

When putting on the SUIT, make completely sure that no sharp objects such as rings, watches or bracelets come into contact with the seals. Please also make sure that when sliding on the seals that the seal openings are pulled apart with both hands to avoid one-sided pressure on the seal.

Cleaning of seals

After every use, rinse all seals with fresh water and apply a Latex care spray on a regular basis.

Storage

Store your suit free of creases, ideally hung up, in a place not lower than 10°C and not higher than 25°C. If the suit is to be stored for a longer period, tuck into wrist and ankle openings.

Wrist and ankle seals have a large contact area in order to maximise water-tightness. For this reason wrist and ankle seals should not be cut. Seals must sit tight and therefore need to get used to. Only Latex neck seals, which have a conical shape, can be cut on the marked trim lines. This, ideally, is to be done with a sharp razor knife.

The zip

Apply the supplied care product to the upper end piece of the zip (at the top stop where the slider sits when the zip is closed) directly before use, then open and close the zip several times. Never exert force on the zip. If the zip gets stuck, open the zip and inspect the teeth for obstructions (hair, fibres etc.) and remove. Only pull the zip in the direction of the zip chain. Strain caused by not pulling the zip in a straight motion could bend teeth and/or cause the slider to fall off. Clean the zip regularly with a soft brush and clear tap water. Do not use solvents. Sharp objects should never be used. After use, close the zip. Bending and folding of the suit can lead to zip damage. Therefore, the zip is to be left closed and crease-free and no objects are to be placed on the suit. A damaged zip can be replaced or repaired by our producer.



HANDCRAFTED IN EUROPE



Mr Jan Gear - www.mrjangear.com - info@mrjangear.com
– The SUIT - care and use instructions. 09/2023

**MR
JAN
GEAR**